

O TEKsys 15" Ecological POS Monitor



Features




1. Spill and Dust proof design in front bezel, ideally for retail and hospitality environment



2. Sturdy and Robust base



3. Two colors logo printing



4. Screen tilting angle freely up to 90 degree vertically



5. Integrate Elo 5 Wires Resistive touch
6. Optional detachable MSR for stock flexibility



7. Optional choices of 2nd display for advertisement application

Specification

| | |
|-------------------------------|---|
| Model | OT15T Series |
| Cabinet Color | Black or White |
| Display Size | 15" |
| Active Area | 304.1 * 228 mm |
| Optimal Resolution | 1024 * 768 |
| Brightness | 250 nits (typ) |
| Contrast Ratio | 600 : 1 |
| Response Time | 8 ms (typ) |
| Viewing Angle(L/R/U/D) | 80 / 80 / 80 / 80 (typ) |
| Input Video Connector | D-Sub 15 pins |
| Power Consumption | 20W |
| Input Frequency | Horizontal : 31.5-60.2 kHz Vertical : 56.3Hz~75 Hz |
| Power Supply | DC 12V +/- 10% |
| Temperature | Operating : 0 °C~40°C Storage : -10°C~50°C |
| Weight (net) | 4.67 kgs |
| Physical Dimension | 365.2(W) * 338.6 (H) * 200 (D) mm |
| Approvals | CE / FCC / CCC / BSMI |
| Touch Technology | 5W Resistive touch |
| Wall Mount type | VESA 75 * 75 |
| Optional Items | |
| Color | Black or White |
| Wall Mount | Bracket |
| MSR | 3 Tracks (ID Tech) |
| 2nd Display | OT07S / OT08S / OT84S / OT84T OT10S |
| Customer Display | VFD |

Dimensions

