



Keypad



MSR



Biometric



Rear Display

- Fanless
- Reliable, retail-hardened construction
- Open operating system architecture
- Compact footprint design
- Low cost of ownership
- Thin-client or thick-client platform
- Fully integrated, plug-and-play system
- Integrated biometric reader, touch display, magnetic strip reader (MSR) and keyboard



PT-5700

wall-mount



The Partner Tech 5700 delivers the answer to today's demanding questions: Fanless, Power, Speed, Reliability and Low Total Cost of Ownership.

The eye pleasing physical appearance of the PT-5700 can be configured with a variety of industry standard peripherals offered by Partner Tech to meet the demands of food-service, specialty retail, and virtually any hospitality environment.

Announcing the New Partner Tech 5700 point of sale solution.

- Proven 2nd generation fanless design
- Small footprint
- Integrated biometrics scanner, card reader and key pad
- Enhanced touch screen technology, capacitive or resistive touch versions
- Ultra fast integrated 10/100/1G network interface
- Open OS architecture for the latest POS software
- Multiple accessory design options to fit your needs

This sleek yet economical POS system is built to work in the typical harsh retail, hospitality and food service environments. It is engineered for easy set-up, quick serviceability and rigorous use that are characteristic of most POS settings. With simple access to connectivity for peripherals and a built-in open architecture to load any software application, the PT-5700 helps lower your total cost of ownership and increase sales efficiency.



As a 20 year old OEM, Partner Tech products and service continually exceeds our customers' expectations.

Specifications

Processor	VIA Eden (V4 Bus) 1GHz CPU @ 400MHz FSB
System Memory	512MB DDR2 SO-DIMM memory up to 1GB, 1 slot
Display	15" Active TFT color LCD
Resolution	1024x768 (optional: 800x600)
Brightness	250 nit
viewing Angle	0° to 60° tilt
Touch Screen	ELO 5-wire resistive or optional capacitive
Network	Ethernet 10/100/1G
Storage	3.5" 80G hard drive
Expansion Options	• Compact flash card socket, IDE interface, • 1 mini-PCI
Power Supply	100~240vAC, DC +19V, 90W power adaptor
I/O Ports	• 4 D-sub 9 RS232 ports provide +5V/12V through jumper free BIOS setting. • 1 parallel port • 1 PS/2 KB • 1 PS/2 mouse • 2 USB 2.0 ports in front, 2 USB 2.0 ports in rear • 1 DB-15 VGA port • 1 RS45 LAN port • 1 RJ-11, 24Vdc cash drawer port supports two cash drawers • 2 Audio ports(1 line-out, 1 MIC-in)
Operating System	Windows 98 / 2000 / XP Pro / XPE / CE.Net / WEPOS / Linux
Peripherals	• Dual or three track magnetic card reader • Biometric Reader, Smart Card Reader, • KB-32 32 key keypad • 2x20VFD customer display
Temperature	• Operating Temperature: 0~40°C • Storage Temperature: -20~60°C
Humidity	• Operating Humidity: -20%~85% • Storage Humidity: -5%~85%
Dimension	• Physical: 10.9x8.5x14.1 inch • Package: 16.1x18.5x15.8 inch
Weight	20.9 lbs
Certification	CE/FCC Class A, UL, cUL, VCCI, BSMI, ROHS

*Specification is subject to change without prior notice

